

TABLE OF CONTENTS

1. Design criteria for DrinTec™ up-flow limestone contactors of constant height	5
1.1 Introduction	5
1.2 Basic concepts of remineralisation	6
1.3 Other effects of remineralisation	6
1.4 Water quality objectives after remineralisation	7
1.5 Up-flow limestone contactors of constant height	8
1.6 Design factors for limestone contactors	10
1.7 Control of remineralisation level	11
2. Empty bed contact time (EBCT)	12
2.1 General concepts	12
2.2 Mathematical simulation of remineralisation	13
3. Temperature effect	14
3.1 Permeate water temperature variations	14
3.2 Effect of temperature on CO ₂ solubility	15
3.3 Effect of temperature on the dissolution of CaCO ₃	16
3.4 Effect of temperature on CO ₂ dose	17
3.5 H ₂ SO ₄ as supplement to CO ₂ dose	18
4. Effect of CO₂ dose	20
4.1 Variation of permeate pH with CO ₂ dose	20
4.2 Estimation of CO ₂ dose from the in situ measurement of permeate pH	20
4.3 Relationship between CO ₂ dose and contact time	22
4.4 Low pressure CO ₂ dissolver	23
4.5 Control of CO ₂ dosing depending on the number of operating racks	25
5. Effect of superficial velocity on contactor's performance	26
5.1 Comparison of the performance of calcite beds at different superficial velocities	26
5.2 Superficial velocity and Reynolds number for calcite beds	28
6. Calcite quality and its effect on bed design and operation	30
6.1 Particle size	30
6.2 Evolution of particle size in the bed over time	31
6.3. Distribution of particles in the bed during the operating phase	32
6.4. Estimation of calcite bed active zone height	33
6.5. Particle size and loss of head in the bed	34
6.6 Recommended calcite quality	35
6.7 Insoluble materials in calcite	36
6.8 Displacement of calcite in DrinTec™ beds	38
6.9 Colour of calcite and effect of iron and manganese content	38
6.10 Calcite biofouling	39
6.11 Growth of algae due to transparent observation windows	40
6.12 Hardness of calcite	41
6.13. Effect of calcite porosity	41
6.14 Roundness	41
6.15. Reactivity of a calcite of organic origin	42
6.16 Effect of humidity on the operation of DrinTec™ beds	43

7. Effect of changes in superficial velocity on the turbidity of treated water	45
7.1 Introduction	45
7.2 Evolution of turbidity in an up-flow plant	47
7.2.1 Case study 1: Intermittent start-ups with new cells in operation	48
7.2.2. Case study 2: Intermittent start-ups without new cells in operation	49
7.3. Daily evolution of turbidity at different operating regimes	50
7.4 Study of the evolution of turbidity in start-ups following shutdowns	55
7.5 Final turbidity in equilibrium phase	59
8. Bed backwashing and blowdown	60
8.1 Introduction	60
8.2 Backwashing and blowdown flows and frequencies	60
8.3 Bed backwashing and blowdown procedure	61
8.4 Volume of water required for bed backwashing	61
8.5 Turbidity of backwashing water	62
9. Partial treatment	65
9.1 Remineralisation with availability of very low cost CO ₂	65
9.2 Remineralisation without availability of low cost CO ₂	66
9.3 Comparative analysis of plants with and without availability of cost-free CO ₂	67
9.4 Consumption of chemical products according to field and simulated data	71
10. Addition of magnesium with remineralisation	73
10.1 Methods for Mg addition with remineralisation	73
10.2. Combined calcite and dolomite treatment with DrinTec™ beds	75
11. Disinfection of remineralised waters	76
11.1 Introduction	76
11.2 Disinfection at different values of pH	76
11.3. Resistance to chlorine of Legionella pneumophila	77
11.4 Remineralised water chlorine demand	78
11.5. Efficiency of disinfection depending on remineralisation treatment	79
11.6 Effect of prolonged aeration on the pH and LSI of remineralised water	80
11.7 Effect of increasing dose of CO ₂ and CaCO ₃ on treatment costs	81
11.8 Conclusions regarding disinfection and CO ₂ dose	81
12. Remineralisation with H₂SO₄ instead of CO₂	83